



# IMPROVED CERTIFICATIONS SEARCH TOOL. REGISTER NOW!

[LEARN MORE](#)

## QMFZ2.E87887 Plastics - Component

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).  
Click on a product designation for complete information.

[Page Bottom](#)

### Plastics - Component

[See General Information for Plastics - Component](#)

**PLASKOLITE LLC**

E87887

1770 JOYCE AVE  
PO BOX 1497  
COLUMBUS, OH 43216-1497 USA

									H	D		
		Min.		H	H	R T I			V	4	C	
		Thk	Flame	W	A	Elec	Mech			T	9	T
Material Dsg	Color	mm	Class	I	I		Imp	Str	R	5	I	
<b>Acrylonite Butadiene Styrene/Polymethyl Methacrylic (ABS/PMMA), furnished as sheets.</b>												
SU(####)	WT	1.5	HB	-	-	50	50	50	-	-	-	
<b>Acrylonitrile Butadiene Styrene/ Polymethyl Methacrylate (ABS/PMMA), furnished as sheets.</b>												
Xtra(f1)	ALL	7.0	HB	-	-	50	50	50	-	-	-	
<b>Polyester (PER), "VIVAK", furnished as sheets.</b>												
VI	NC	1.5	HB	-	-	50	50	50	-	-	-	
VU(f1)	NC	1.5	HB	-	-	50	50	50	-	-	-	
<b>Polymethy Methacrylate, furnished as sheets.</b>												
XL1(f1)	WT, IV, GY, BL	1.5	HB	-	-	50	50	50	-	-	-	
<b>Polymethyl Methacrylate (PMMA), "Optix", furnished as sheets.</b>												
<b>L(@)(f1), Optix L(f1)</b>												
	CL	1.5	HB	-	-	50	50	50	-	-	-	
<b>L(@)(f2), Optix L(f2)</b>												
	ALL	1.5	HB	-	-	50	50	50	-	-	-	
<b>XL(@) GR(####)(f1) or Optix XL Granite</b>												
	ALL	1.5	HB	-	-	50	50	50	-	-	-	
<b>XL(@)(f2), Optix XL(f2)</b>												
	ALL	1.5	HB	-	-	50	50	50	-	-	-	

<b>Polymethyl Methacrylate (PMMA), furnished as pellets.</b>											
<b>DURAPLEX</b>	NC	1.5	HB	-	-	50	50	50	0	5	0
		3.0	HB	3	0	50	50	50			
		6.0	HB	1	0	50	50	50			
<b>MS-983 Acrylic (f1)</b>											
	NC	1.5	HB	-	-	90	90	90	-	-	-
<b>PL-(a)(f2)(b)</b>	NC	1.5	HB	3	0	90	90	90	0	6	0
		2.2-2.4	HB, RP200	3	0	90	90	90			
		3.0	HB	2	0	90	90	90			
<b>PL-(a)UVA(f2)(b)</b>	NC	1.5	HB	3	0	90	90	90	0	6	0
		2.2-2.4	HB, RP200	3	0	90	90	90			
		3.0	HB	2	0	90	90	90			
<b>Polymethyl Methacrylate (PMMA), furnished as sheets.</b>											
<b>AB GR(####)(f1)</b>	ALL	1.5	HB	-	-	50	50	50	-	-	-
<b>AB(f1)</b>	WT	1.5	HB	-	-	50	50	50	-	-	-
<b>DURAPLEX 100%I</b>	CL	1.5	HB	4	0	90	90	90	-	-	-
<b>DURAPLEX 50%I</b>	CL	1.5	HB	4	0	90	90	90	-	-	-
<b>DURAPLEX 70%I</b>	CL	1.5	HB	4	0	90	90	90	-	-	-
<b>OPTIX (f1)</b>	CL	1.5	HB	4	0	90	90	90	0	5	0
		3.0	HB	3	0	90	90	90			
<b>XL1(f2)</b>	ALL	1.5	HB	-	-	50	50	50	-	-	-
<b>XL2</b>	WT	1.5	HB	-	-	50	50	50	-	-	-

(####) - Represents four numeric characters denoting the color code

(@) - May be followed by three to five alphanumeric characters that represent inside designations

(a) - Replaced with two or three integers 22 to 150 incl.

(b) - ASTM E162 (Radiant Panel) : Flame spread index: Less than 200; Sustained Flaming: 381 mm; Dripping: Yes (Flaming)

(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

(f2) - Subjected to one or more of the following tests: Ultraviolet Light, Water Exposure or Immersion in accordance with UL 746C, where the acceptability for outdoor use is to be determined by UL.

Marking: Company name and material designation on container, wrapper or finished part.

Last Updated on 2018-09-23

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".