

# PLASKOLITE

## ACRYLIC STANDARD REEL LENGTHS AND WIDTHS

<u>Gauge</u>	<u>Industry Standard</u>	<u>Invoiced Width (in)</u>	<u>Supplied Width (in)</u>	<u>Length (ft)</u>	<u>Weight (lbs)</u>	<u>Material Total (sf)</u>	<u>Masking Coverage</u>	<u>Tolerance Min-Max</u>
0.118	3 Foot	39	39	500	1086	1,625	39"	39"-4088"
0.118	4 Foot	52	52	500	1448	2166	52"	52"-53"
0.118	5 Foot	63	63	500	1754	2625	63"	63"-64"
0.118	6 Foot	78	78	500	2171	3250	78"	78"-79"
0.118	8 Foot	100	100	500	2784	4166	100"	100"-101"
0.150	3 Foot	39	39	400	1166	1300	39"	39"-40"
0.150	4 Foot	52	52	400	1555	1734	52"	52"-53"
0.150	5 Foot	63	63	400	1884	2100	63"	63"-64"
0.150	6 Foot	78	78	400	2332	2600	78"	78"-79"
0.150	8 Foot	100	100	400	2990	3,333	100"	100"-101"
0.177	3 Foot	39	39	350	1133	1137	39"	39"-40"
0.177	4 Foot	52	52	350	1511	1517	52"	52"-53"
0.177	5 Foot	63	63	350	1831	1837	63"	63"-64"
0.177	6 Foot	78	78	350	2266	2275	78"	78"-79"
0.177	8 Foot	100	100	350	2905	2916	100"	100"-101"

Note: There is a 3,000 LB minimum for 0.093" reels- 625 ft, and 0.236" reels- 250ft.

**DISCLAIMER:**

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale.