



THE IDEAL COMBINATION OF DURABILITY, FORMABILITY AND STRENGTH

Utility grade ABS (Acrylonitrile Butadiene Styrene) sheet is extruded with the highest quality regrind and 100% virgin cap. ABS is stocked with one side Haircell and the other smooth, with gauges available from 0.060" - 0.236". It has outstanding formability, high impact strength, and durability.

Custom color matching and sizes available

Features

- » Outstanding molding and fabrication
- » Rigid and creep resistant
- » Run to size - 3000 pound minimum

Applications

- » Automotive
- » Dunnage
- » Containers

Item #	Colors	Pattern/Textures	Masking	Thickness (in.)	Size (in.)	Sq. Ft.	Skid Qty.
ABS2103C	White	Haircell/Smooth	None	0.060	48 x 96	32	125
ABS9900A	Black	Haircell/Smooth	None	0.060	48 x 96	32	125
ABS2104C	White	Haircell/Smooth	None	0.093	48 x 96	32	75
ABS9901A	Black	Haircell/Smooth	None	0.093	48 x 96	32	75
ABS2105C	White	Haircell/Smooth	None	0.118	48 x 96	32	60
ABS9902A	Black	Haircell/Smooth	None	0.118	48 x 96	32	60
ABS2106C	White	Haircell/Smooth	None	0.117	48 x 96	32	40
ABS9903A	Black	Haircell/Smooth	None	0.117	48 x 96	32	40
ABS2107C	White	Haircell/Smooth	None	0.236	48 x 96	32	30
ABS9904A	Black	Haircell/Smooth	None	0.236	48 x 96	32	30

PLASKOLITE

400 Nationwide Blvd, Suite 400
Columbus, OH 43215
800.848.9124 • Fax: 877.538.0754
plaskolite@plaskolite.com
www.plaskolite.com