



THE IDEAL MASKING FOR FABRICATORS

NO PAPER, NO ADHESIVES - ALLOWS YOU TO CUT, BEND AND POLISH WITHOUT REMOVING THE MASKING - AT NO ADDITIONAL COST TO YOU

Added protection during the fabricating process

- » TufGuard[®] allows OPTIX[®] L acrylic sheet to be precision cut and heat bent, while the masking remains on the entire surface of the sheet

Ease of use from sheet to finished product

- » TufGuard masking is also writeable, reclingable, recyclable and tear-resistant, adding convenience, protection and productivity to every aspect of your manufacturing process

Protection during shipping and storage

- » Stronger and far more versatile than traditional masking
- » TufGuard provides excellent protection from scratching
- » Resists the negative effects of temperature and humidity - longer storage life

Ask for TufGuard in your next acrylic design

Skid Quantities for sheet size and thickness

Sheet size	Thickness							
	0.080"	0.098"	0.118"	0.177"	0.220"	0.236"	0.315"	0.354"
48 x 96	125	100	80	55	45	40	35	32
60 x 96	-	-	75	50	45	45	25	23
72 x 96	-	-	65	45	35	35	22	19
51 x 100	-	-	80	50	35	35	28	25

PLASKOLITE

400 Nationwide Blvd, Suite 400
Columbus, OH 43215
800.848.9124 • Fax: 877.538.0754
plaskolite@plaskolite.com
www.plaskolite.com