SAFETY DATA SHEET OPTIX® XL Sheet

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Trade Name: OPTIX® XL Sheet

Other Names: XL Solid, Granite, Marble, Serenity Series, Gemstone, Lustre, Lustre

Marble, formerly known as Lucite® XL

Usage: Surface material for sanitary ware (bath, shower, sinks, and spas).

Supplier: Plaskolite, LLC.

400 West Nationwide Boulevard, Suite 400, Columbus, Ohio 43215, USA

Telephone: 800-848-9124 www.plaskolite.com

Emergency Telephone: 800-848-9124

2. HAZARDS IDENTIFICATION

This material is classified as not hazardous under OSHA regulations. Not classified as dangerous for supply/use. Low toxicity under normal conditions of handling and use. Combustion or thermal decomposition will evolve toxic, irritant and flammable vapors. Care should be taken during thermoforming to ensure that the product is not exposed to temperatures exceeding 392°F (200°C). Certain machining operations (e.g. laser cutting) can give rise to toxic and corrosive fumes. Adequate ventilation MUST be used.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Characterization: ~97% Poly(methyl methacrylate/butyl acrylate) [CAS# 25852-37-3]

~1% Methyl methacrylate [CAS# 80-62-6]

4. FIRST AID MEASURES

Inhalation: Dust or fumes from fabrication operations may cause irritation, IF INHALED:

Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

Skin Contact: Unlikely to cause skin irritation. IF ON SKIN: Wash with plenty of soap and

water. If skin irritation or rash occurs: Get medical attention.

Eye Contact: Dust or fumes from fabrication operations may cause irritation. IF IN EYES:

Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Ingestion: Low oral toxicity. Do not induce vomiting. Rinse mouth.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Water spray, foam, dry powder or CO2.

Specific Fire Hazards: Combustion will evolve toxic, irritant and flammable vapors.

SAFETY DATA SHEET OPTIX® XL Sheet

Special Protective Equipment &

Precaution for Fire Fighters: A self-contained breathing apparatus and suitable protective clothing should

be worn in fire conditions.

6. ACCIDENTAL RELEASE MEASURES

Personal Precaution: Provide adequate ventilation. Wear personal protection equipment. Do not

breathe dust.

Environmental Precaution: Do not allow to enter into soil, waterbodies or drains.

Methods for Cleaning Up: Offcuts, swarf or dust should be collected and disposed of in a safe way.

7. HANDLING AND STORAGE

Max. Storage Temperature: < 104°F (< 40°C)

Handling: These sheets are heavy and unwieldy. They should be handled with care,

particularly in windy locations or outdoors. If broken or chipped the resultant edges can be sharp and cause cuts to skin and eyes. Take precautionary measures against static discharges. All polymers degrade to some extent at their processing temperature, an effect which increases with increasing temperature. Under normal conditions where thermoforming temperatures will not exceed 392°F (200°C) thermal decomposition products will include methyl methacrylate. Local exhaust ventilation and/or respiratory protective equipment should be used. Certain machining operations (e.g. laser cutting) can give rise to toxic and corrosive fumes. Adequate ventilation MUST be

used.

Storage: Keep away from heat. Store vertically on A-frames. Indefinite storage life

under specified storage conditions.

Incompatible materials: Most organic solvents, acetone, chlorinated hydrocarbons.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation Measures: Provide good ventilation and/or an exhaust system in the work area.

Respiratory Protection: None required under normal conditions.

Hand Protection: Wear suitable gloves. Sharp edges may cause cuts.

Eye Protection: Safety glasses with side shields (ANSI Z87.1 equivalent).

Skin & Body Protection: Wear suitable protective clothing and boots. Sharp edges may cause cuts.

SAFETY DATA SHEET OPTIX® XL Sheet

Other Protective Measures: Do not eat, drink or smoke at the work place. Provide adequate ventilation,

including appropriate local extraction if dusts, fumes or vapors are likely to be evolved. Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required. Local extraction close to the cutting head must be used when laser cutting. When thermoforming local exhaust ventilation should be used. Where suitable engineering controls are not

fitted or are inadequate, wear suitable protective equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Solid sheets
Color: Clear or colored

Odor: Odorless pH: Not applicable Melting Point: Not available **Boiling Point:** Not available Decomposition Temperature: Not available Flash Point: Not available Auto-ignition Temperature: Not available **Explosion Limits:** Not applicable **Evaporation Rate:** Not applicable Vapor Pressure: Not applicable Vapor Density: Not applicable

Relative Density: 1.19
Solubility (Water): Insoluble

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions. Hazardous polymerization does not occur.

Conditions to Avoid: Protect from excessive heat. Keep away from sources of ignition and heat.

Avoid dust formation.

Materials to Avoid: Most organic solvents, acetone, chlorinated hydrocarbons

Hazardous Decomposition

Products: Thermal decomposition or combustion may emit vapors, carbon monoxide,

or carbon dioxide.

11. TOXICOLOGICAL INFORMATION

This product should not be harmful under normal conditions of use.

Inhalation: Unlikely to be harmful by inhalation under ambient temperature. Inhalation

of vapors from heated product can cause nausea, headache, dizziness as

well as irritation of lungs, nose, and throat.

Skin Contact: No evidence of irritant effects from normal handling and use. Sharp edges

may cause cuts.

Ingestion: Unlikely to be harmful by ingestion under ambient temperature.

SAFETY DATA SHEET OPTIX® XL Sheet

Eye Contact: Vapors from heated product can irritate the eyes. Sharp off-cuts may cause

eye damage.

Carcinogenity: Non-carcinogenic

12. ECOLOGICAL INFORMATION

Ecotoxicity: This product should have low toxicity to aquatic and terrestrial organisms.

Mobility: Due to the solid nature of this product, it should have low mobility in soil.

Persistence & Degradability: This product is non-biodegradable.

Bioaccumulation: This solid product has a low potential for bioaccumulation.

13. DISPOSAL CONSIDERATIONS

Waste disposal should be in accordance with all federal, state and local environmental laws and regulations.

14. TRANSPORT INFORMATION

Not subject to national and international regulations on the transport of dangerous goods.

15. REGULATORY INFORMATION

OSHA Hazard Communication: Non-hazardous

Toxic Substances Control Act: Listed

CERCLA Hazardous

Substances (40 CFR 302): None

SARA Section 313 Toxic

Chemicals (40 CFR 372.65): None

EU Regulations: This product is an Article and as such Article 31 (Requirements for Safety

Data Sheets) of Regulation (EC) #1907/2006 does not apply.

California Proposition 65: This product does not require a warning about chemicals known to the state

of California to cause cancer and birth defects or other reproductive harm.

Canada (DSL/NDSL): Listed in DSL

Japan (ENCS): Listed

Philippines (PICCS): Listed

Australia (AICS): Listed

South Korea (KECI): Listed

China (IECSC): Listed

SAFETY DATA SHEET OPTIX® XL Sheet

16. OTHER INFORMATION

SDS Prepared By: Plaskolite Environmental, Health & Safety

SDS Original Date of Preparation: May 3, 2018

SDS Revision Date: February 10, 2023

The information presented herein is believed to be factual and reliable. It is offered in good faith, but without guarantee, since conditions and methods for the use of our products are beyond our control. We recommend that the prospective user determine the suitability of our products and these suggestions before adopting them on a commercial scale.

Filename: SDS - Optix XL Sheet.doc