

PLASKOLITE

TUFFAK® STANDARD REEL LENGTHS AND WIDTHS

<u>Gauge</u>	<u>Industry Standard</u>	<u>Invoiced Width (in)</u>	<u>Supplied Width (in)</u>	<u>Length (ft)</u>	<u>Weight (lbs)</u>	<u>Material Total (sf)</u>	<u>Masking Coverage</u>	<u>Tolerance Min-Max</u>
0.118	3 Foot	40	42	600	1545	2,000	40"	44"-45"
0.118	4 Foot	52	55	600	2023	2,600	52"	55"-57"
0.118	5 Foot	64	67	600	2465	3,200	64"	67"-69"
0.118	6 Foot	76	78	500	2330	3,167	76"	77"-79"
0.118	8 Foot	100	102	450	2759	3,750	96"	102"-105"
0.150	3 Foot	40	42	500	1637	1,667	40"	44"-45"
0.150	4 Foot	52	55	500	2143	2,167	52"	55"-57"
0.150	5 Foot	64	67	500	2611	2,667	64"	67"-69"
0.150	6 Foot	76	78	450	2666	2,850	76"	77"-79"
0.150	8 Foot	100	102	400	3118	3,333	96"	102"-105"
0.177	3 Foot	40	42	400	1545	1,333	40"	44"-45"
0.177	4 Foot	52	55	400	2023	1,733	52"	55"-57"
0.177	5 Foot	64	67	400	2465	2,133	64"	67"-69"
0.177	6 Foot	76	78	350	2446	2,217	76"	77"-79"
0.177	8 Foot	100	102	325	2989	2,708	96"	102"-105"

Note: There is a 3,000 LB minimum for 0.093" reels- 625 ft, and 0.236" reels- 250ft.

DISCLAIMER:

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale.