

PLASKOLITE

POUNDS Per SQUARE FOOT

| Gauge | PRODUCT | | | | | | |
|-------|---------|-------------------------|----------------------------------|-----------------|---------------------------|--------------------------|--|
| | TUFFAK® | TUFFAK® Prismatic (P12) | TUFFAK® Skylight Prismatic - SK1 | TUFFAK® MG & WG | Hygard® Containment Grade | Hygard® Bullet Resistant | |
| .020 | .125 | | | | | | |
| .030 | .187 | | | | | | |
| .040 | .250 | | | | | | |
| .060 | .374 | | | | | | |
| .080 | .499 | | | | | | |
| .093 | .580 | | | | | | |
| .100 | | | | | | | |
| .110 | | .4412 | .3238 | | | | |
| .118 | .736 | .4911 | | | | | |
| .125 | .780 | .5348 | .4209 | | | | |
| .150 | .936 | .6904 | .5820 | | | | |
| .156 | | .7287 | | | | | |
| .165 | | | .6768 | | | | |
| .177 | 1.104 | .8590 | .7540 | | | | |
| .187 | 1.167 | .9220 | | | | | |
| .220 | 1.373 | 1.1270 | | | | | |
| .236 | 1.473 | | | | | | |
| .375 | 2.340 | | | | 2.40 | | |
| .500 | 3.120 | | | | 3.30 | | |
| .750 | | | | 4.860 | 4.90 | 5.10 | |
| 1.000 | | | | 6.480 | | 6.50 | |
| 1.250 | | | | 8.100 | | 8.10 | |
| 1.500 | | | | 9.720 | | | |
| 1.750 | | | | 11.340 | | | |
| 2.000 | | | | 12.960 | | | |

PRODUCT
TUFFAK®
Hygard®

FACTOR
6.24
6.24

FORMULA

Gauge x Factor = LBS per SQ/FT

Prismatic Weight Factors differ with each gauge. Call Inside Sales for unlisted weights